



### 1-port Gigabit IEEE 802.3at/af PoE Injector

- 1 Ethernet Input Port (Data Only)
- 1 Ethernet Output Port (Data + Power)
- Compliant with IEEE 802.3at and IEEE802.3af
- Smart Plug and Play -- Build-in power

### Introduction

INEO-01PJGL is 1 Ethernet Input (data only) port and 1 Output (data + power) port Power over Ethernet Injector that is designed for small or medium network environment to strengthen its network connection. This product can convert standard 90~260V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3at/af compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3at compliant, or only the data will be sent through LAN cable. By adding INEO-01PJGL to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

### No Special Networking Cable Required

By adding PoE devices, you can use an existing standard Cat-5 Ethernet cable to deliver both power and data where power source is difficult to obtain. It helps you reduce installation time and cost.

## Technical Specifications

<b>Standards</b>	IEEE802.3at/af PoE IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T
<b>Features</b>	Number of Ports: 1 Ethernet Input (data only) RJ-45 port 1 Ethernet Output (data + power) RJ-45 port
<b>Led Indicators</b>	Per Unit: Power
<b>Power Input</b>	90~260V/AC, 50~60Hz
<b>Power Output</b>	48V/DC at Full 25~30W Output Supported
<b>Power Consumption</b>	35 Watts (Max)
<b>Dimensions</b>	160 × 50 × 30 mm (L x W x H)
<b>Weight</b>	0.23 kg
<b>Operating Temperature</b>	0 to 40°C
<b>Storage Temperature</b>	-20 to 85°C
<b>Humidity</b>	10 to 90% RH (non-condensing)
<b>Certifications</b>	FCC Class A, CE