



- 8-port 10/100/1000M PoE+ and 2 Gigabit TP/SFP combo ports
- Comply with IEEE 802.3af/at up to 30W High Power PoE
- Multiple event relay output for enhanced device alarm control
- Industrial heat dispersing design, -40~75°C wide operating temperature
- SNMP trap and SysLog
- Advanced management by LACP/VLAN/ Private VLAN / QinQ / QoS/ IGMP Snooping/Rate Control/ Online Multi-Port Mirroring/DHCP
- Cisco-Like management e CLI, Web, SNMP/RMON for network
- Voice VLAN
- Static Routing
- IEEE 1588v2 Precision Time Protocol (PTP)

Industrial 8-port 10/100/1000M PoE+ Full Managed Switch with 2 Combo TP/SFP Uplink Ports

Introduction

INEO-IGM0802P is a DIN Rail type industrial Gigabit managed Power over Ethernet Switch is designed with eight 10/100/1000M PoE+ ports and two Gigabit TP/ SFP combo ports for highly critical PoE applications such as real time IP video surveillance, WiMAX systems and Wireless APs. All of the 8 ports of the switch are compliant with both IEEE 802.3af PoE and IEEE 802.3at high power PoE standards and can deliver up to 15.4W and 30W power per port to enable the high-power requiring devices, such as Wireless APs, PTZ and dome network cameras, etc.

The two Gigabit Ethernet combo ports provide high speed uplink to connect with higher level backbone switches with ERPS (Ethernet Ring Protection Switching) technology, while ensuring the reliability of video transfer through the exclusive 50ms recovery time. By supporting various connection types, including 10/100/1000Mbps RJ-45 copper or 100Mbps, 1000Mbps Fiber, the Gigabit uplink ports further enlarge the ring infrastructure.

With Industrial EMC certified design, including robust enclosure and -40~70°C wide operating temperature range, this switch ensures high performance of the surveillance network under vibrating and shock environments in rolling stocks, traffic control systems and other harsh surveillance applications.

Redundant Power Inputs & Embedded Protecting Circuit

INEO-IGM0802P provides two power inputs that can be connected simultaneously to live DC power source. If one of the power input fails, the other live source acts as a backup to automatically support the switch's power needs without compromising network service qualities. Also, it supports automatic protection switching and load balance, while its embedded protecting circuit can protect your system from over input/output voltages and rectifier malfunctions.

2 Gigabit RJ45 Copper/SFP Combo Ports

INEO-IGM0802P supports 2 Gigabit Copper/SFP Combo Ports to uplink to servers, storage, or other switching devices for long loop reach applications.

Outstanding Management and Enhanced Security

This switch provides various network control and security features to ensure the reliable and secure network connection. To optimize the industrial network environment the switch supports advanced network features, such as Tag VLAN, Private VLAN, QinQ, IGMP Snooping, Quality of Service (QoS), Link Aggregation Control Protocol (LACP), Rate Control, etc. The PoE switch can be smartly configured through Web Browser, SNMP Telnet and RS-232 local console with its command like interface. The failure notifications are sent through e-mail, SNMP trap, Local/Remote system log, multiple event alarm relay.

To avoid hacker's attacks and ensure the secure data transmission, this switch features DHCP client, DHCP server with IP and MAC binding, 802.1X Access Control, SSH for Telnet security, IP Access table, port security and many other security features.

Technical Specifications

Interface

- 10/100/1000 Base RJ45 PoE Ports : 8
- 100/1000Base-X SFP and 1000 RJ45 Combo Port : 2
- Console Port for CLI Management : 1

Mechanical

- DC 44~57V : Dual Redundant
- Dimension (HxWxD) : 175x74x125 mm
- LED : Power 1 & 2, Fault, Link/Act, PoE, SFP
- Operating Temperature : -40 to 75°C
- Storage Temperature : -40~85°C
- Operating Humidity : 5~95% (non-condensing)
- Alarm Contact : 1 relay output with current carrying capacity of 1A @ 24 VDC
- Reverse Polarity Protection
- Overload Current Protection
- CPU Watch Dog
- Casing : IP30 protection, aluminum alloy case
- EMI : FCC Part 15 Subpart B Class A, EN 55022 Class A, VCCI Class A
- EMS
 - EN61000-4-2 (ESD) EN61000-4-3 (RS)
 - EN61000-4-4 (EFT) EN61000-4-5 (Surge)
 - Level 4 (DC in), RJ45 Line to Ground
 - EN61000-4-6 (CS)
 - Level 3
 - EN61000-4-8
 - EN61000-4-11
- Shock : IEC60068-2-27
- Free Fall : IEC60068-2-32

Security

- Management System User Name/Password Protection
- User Privilege : Set user privilege up to 15 Level
- Port Security (MAC-based)
- IEEE 802.1x Port-based Access Control
- ACL (L2/L3/L4)
- IP Source Guard
- RADIUS (Authentication, Authorization, Accounting)
- TACACS+
- HTTP & SSL (Secure Web)
- SSH v2.0 (Secured Telnet Session)
- MAC/IP Filter

Management

- Command Line Interface (CLI)
- Web Based Management
- Telnet
- Access Management Filtering : SNMP/WEB/SSH/TELNET
- Firmware Upgrade via HTTP
- Dual Firmware Images
- Configuration Download/Upload
- SNMP (v1/v2c/v3)
- RMON (1,2,3,&9 groups)
- DHCP (Server/Client/Relay/Option82/Snooping)
- System Event/Error Log
- NTP/LLDP
- Cable Diagnostics
- IPv6 Configuration

- Vibration : IEC60068-2-6
- Installation : DIN-Rail mounting or Wall mount (Optional)

L2 Features

- Auto-negotiation
- Auto MDI/MDIX
- Flow Control (Duplex) :
 - 802.3x (Full)
 - Back-Pressure (Half)
- Spanning Tree :
 - IEEE 802.1D (STP)
 - IEEE 802.1w (RSTP)
 - IEEE 802.1s (MSTP)
- VLAN
 - VLAN Group : 4K
 - Tagged Based
 - Port-based
 - Voice VLAN
- Link Aggregation :
 - IEEE 802.3ad with LACP
 - Static Trunk
 - Max. LACP Link Aggregation Group : 5
- IGMP Snooping :
 - IGMP Snooping v1/v2/v3 : Supports 1024 IGMP groups
 - IGMP Static Multicast Addresses : Supports 1024 static multicast addresses
 - IPv6 MLD Snooping : Supports 1024 MLD groups
 - MLD Static Multicast Addresses : Supports 1024 static multicast addresses
 - Querier, Immediate Leave
- IEEE 1588v2 - Precision Time Protocol (PTP)
- Storm Control (Broadcast/Multi-cast/Un-known Unicast)
- Carrier Sense Multiple Access with Collision Detection (CSMA/CD) RFC 903 - Reverse Address Resolution Protocol (RARP)
- G.8032 - Ethernet Ring Protection Switching (ERPS)
- Jumbo Frame Support : 9.6KB

QoS Features

- Number of priority queue : 8 queues/port
- Rate Limiting :
 - Ingress : 1KBps/1pps
 - Egress : 1KBps/1pps
- DiffServ (RFC2474 Remarking)
- Scheduling (WRR, Strict, Hybrid)
- CoS
 - IEEE 802.1p
 - IP ToS precedence, IP DSCP

- Port Mirroring : One to One or Many to One

Standard

- IEEE 802.3 - 10BaseT
- IEEE 802.3u - 100BaseTX
- IEEE 802.3ab - 1000BaseT
- IEEE 802.3z 1000BaseSX/LX
- IEEE 802.3af Power over Ethernet (PoE)
- IEEE 802.3at Power over Ethernet (PoE+)
- IEEE 802.3az - Energy Efficient Ethernet (EEE)
 - IEEE 802.3x - Flow Control
- IEEE 802.1Q - VLAN
 - IEEE802.1v - Protocol VLAN
- IEEE 802.1p - Class of Service
- IEEE 802.1D - Spanning Tree
 - IEEE 802.1w - Rapid Spanning Tree
 - IEEE 802.1s - Multiple Spanning Tree
- IEEE 802.3ad - Link Aggregation Control Protocol (LACP)
- IEEE 802.1AB - LLDP (Link Layer Discovery Protocol)
- IEEE 802.1X - Access Control
- IEEE 1588v2 - Precision Time Protocol (PTP)
- Carrier Sense Multiple Access with Collision Detection (CSMA/CD)
- RFC 903 - Reverse Address Resolution Protocol (RARP)
- G.8032 - Ethernet Ring Protection Switching (ERPS)

System Performance

- Packet Buffer : 4Mbits
- MAC Address Table Size : 8K
- Switching Capacity : 20Gbps
- Forwarding Rate : 14.88Mpps

PoE Features

- IEEE 802.3 af/at
- Number of PSE Ports : 8
- System Power Consumption : 15W
- Power Feeding Detecting Capability on PD
- PD Classification
- Power Management (per-port) :
 - Enable/Disable PoE Per Port
 - Priority Setting Per Port
 - Power Level Setting Per Port
 - Overloading Protection

tactio™

Rev.1.01

tactio™
<http://www.tactio.net>