



48-port 10/100M Rack-mount Fast Ethernet Switch

- 19" Standard Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Internal Power Supply

Technical Specifications

- **Standard**
 - IEEE 802.3 10BaseT
 - IEEE 802.3u 100BaseTX
 - IEEE 802.3x Full-duplex and Flow Control
- **Number of Port**
 - 48-port 10/100BaseT(X)
- **Mechanical :**
 - LED Indicator
 - Per Port: Link / Act, 10/100M
 - Per Unit: Power
- **Power Consumption**
 - 15 Watts (Max)
- **Power Supply**
 - 100~240V/AC, 50~60Hz
- **Product Dimensions / Weight**
 - 440 × 220 × 44 mm (L x W x H) / 3.2kg
- **Environmental Specification:**
 - Operating Temperature : 0 to 55 °C
 - Storage Temperature : -20 to 90 °C
 - Humidity : 10 to 90% RH (non-condensing)
- **Performance**
 - MAC Address: 8K
 - Buffer Memory: 2.5Mb
 - Transmission Method: Store and Forward
- **Package Contain**
 - Power Cord
 - User Manual
 - Rack-mount kit
- **N.W / G.W**
 - 15 kg / 16 kg
- **Certification**
 - FCC Class A, CE