



- 24 x Gigabit Ethernet ports with IEEE 802.3at PoE+ & 4 Gigabit SFP Slot
- Built for harsh environments and -40~75°C wide temperature range application
- RSTP, ERPS, LACP for Network Redundancy
- QoS CoS/DSCP to increase determinism
- Supports IGMP Snooping v1/v2, up to 1023 groups
- DHCP Relay Option 82 for policies IP address assignment
- SNMP v1/v2c/v3 for network management
- Supports Storm Protection
- USB storage for configuration-free replacement
- Support industrial automation protocol Modbus TCP
- Supports PoE PD Alive Check Function for PoE Device Power Recycle

Industrial 24-port 10/100/1000M PoE+ with 4 Giga SFP Slots Switch

Introduction

This switch is an industrial Gigabit managed Power over Ethernet Switch is designed with 24 10/100/1000M PoE+ ports and 4 Gigabit SFP slots for highly critical PoE applications such as real time IP video surveillance, WiMAX systems and Wireless APs. All of the 24 ports of the switch are compliant with both IEEE 802.3af PoE and IEEE 802.3at high power PoE standards and can deliver up to 15.4W and 30W power per port to enable the high-power requiring devices, such as Wireless Aps, PTZ and dome network cameras, etc.

4 Gigabit SFP Ports

INEO-IGM2440P supports 4 Gigabit SFP Ports to uplink to servers, storage, or other switching devices for long loop reach applications.

Ethernet Ring Protection Switching (ERPSv2)

Ring network topology ensures the reliability of the connections among all the switches in the network. INEO-IGM2440P supports ERPSv2 with easy to set up user interface, which allows it to recover from network disconnection in less than 20ms with 250 INEO-IGM2440P connected in a ring network topology while transmitting/receiving data at full network speed. Also, INEO-IGM2440P supports multiple ERPS instances, allowing different VLANs have their own ERPS instances.

USB Port for Save/Restore Configuration & System Log/Firmware Storage

INEO-IGM2440P comes with a USB port for connecting a USB storage device to the industrial switch. Configuration files, switch system log and firmware can be stored in the USB storage device for the switch to access. When a USB storage device is connected to INEO-IGM2440P, it will load the configuration file in the storage device and apply all the settings, saving on-site installation time and effort.

Outstanding Management and Enhanced Security

This switch provides various network control and security features to ensure the reliable and secure network connection. To optimize the industrial network environment the switch supports advanced network features, such as Tag VLAN, IGMP Snooping, Quality of Service (QoS), Link Aggregation Control Protocol (LACP), Rate Control, etc. The PoE switch can be smartly configured through Web Browser, SNMP Telnet and RS-232 local console with its command like interface. The failure notifications are sent through e-mail, SNMP trap, Local/Remote system log, multiple event alarm relay.

Technical Specifications

Interface

- 10/100/1000 Base RJ45 Ports : 24
- Gigabit Uplink SFP Slot : 4
- Console Port for CLI Management : 1
- USB Port : 1x USB 2.0 storage for firmware update, configuration backup, restore, boot up and system log
- DI/DO

QoS Features

- CoS
- DSCP
- WRR/SPQ Queuing
- Storm Control

L2 Features

- Auto-negotiation
- Auto MDI/MDIX
- Flow Control (Duplex) :
 - 802.3x (Full)
 - Back-Pressure (Half)
- Spanning Tree :
 - IEEE 802.1D (STP)
 - IEEE 802.1w (RSTP)
 - IEEE 802.1s (MSTP)
- VLAN :
 - VLAN Group : 4K
 - Tagged Based
 - Port-based
 - Voice VLAN
- Link Aggregation : IEEE 802.3ad with LACP
- IGMP Snooping :
 - IGMP Snooping v1/v2/v3 : Supports 1023 IGMP groups
 - IGMP Static Multicast Addresses
 - Querier, Immediate Leave
- Storm Control
- G.8032 - Ethernet Ring Protection Switching (ERPS)
- Jumbo Frame Support : 16,000 Byte

System Performance

- Packet Buffer : 12Mbits
- MAC Address Table Size : 16K
- Switching Capacity : 56Gbps
- Forwarding Rate : 41.664Mpps

Standard

- IEEE 802.3 - 10BaseT
- IEEE 802.3u - 100BaseTX
- IEEE 802.3ab - 1000BaseT
- IEEE 802.3z - 1000BaseSX/LX
- IEEE 802.3af - PoE
- IEEE 802.3at - PoE+
- IEEE 802.3x - Flow Control
- IEEE 802.1Q - VLAN
- IEEE 802.1p - Class of Service
- IEEE 802.1D - Spanning Tree
- IEEE 802.1w - Rapid Spanning Tree
- IEEE 802.1s - Multiple Spanning Tree
- IEEE 802.3ad - Link Aggregation Control Protocol (LACP)
- IEEE 802.1AB - LLDP (Link Layer Discovery Protocol)
- IEEE 802.1X - Access Control
- ITU-T G.8032/Y.1344 - Ethernet Ring Protection Switching (ERPS)

Management

- Command Line Interface (CLI)
- Web Based Management
- Telnet
- Firmware Upgrade via HTTP
- Configuration Download/Upload
- SNMP (v1/v2c/v3)
- RMON (1,2,3,&9 groups)
- DHCP (Server/Client/Relay/Option82)
- System Event/Error Log
- NTP/LLDP
- Port Mirroring
- Industrial Profiles : Modbus TCP & Ethernet/IP
- Time Sync. : NTP, IEEE1588v2 OC (Software Timestamp), TC (Hardware Timestamp)

Industrial Standard

- Reverse Polarity Protection
- Overload Current Protection
- Casing : IP40 protection, aluminum alloy case
- EMI : FCC Part 15 Subpart B Class A, CE EN 55022 Class A
- EMS
 - IEC61000-4-2 (ESD Level 4), IEC61000-4-3 (RS Level 3)
 - IEC61000-4-4 (EFT Level 4), IEC61000-4-5 (Surge Level 4)
 - IEC61000-4-6 (CS Level 3), IEC61000-4-8 (Magnetic Field Level 4), IEC-61850-3
- Shock : IEC60068-2-27
- Free Fall : IEC60068-2-32
- Vibration : IEC60068-2-6
- Green : RoHS Compliant

Security

- Management System User Name/Password Protection
- IEEE 802.1x Port-based Access Control
- RADIUS (Authentication, Authorization, Accounting)
- HTTP & SSL (Secure Web)
- SSH v2.0 (Secured Telnet Session)

Mechanical

- Input Power : 90~264VAC, 48~57VDC, Redundant Dual Inputs
- Dimension (HxWxD) : 440 x 44 x 331 mm
- Weight : 6KG
- LED :
 - Per unit : PWR1, PWR2, Fault, Ring Master, Ring State
 - Ports : Link/Active with highest speed (Green), low speed (Amber)
 - PoE : Output Power
- Button : 1 multiple function reset button
- Operating Temperature : -40 to 75°C
- Storage Temperature : -40 to 85°C
- Operating Humidity : 5~95% (non-condensing)
- MTBF : >100,000 Hours

PoE Features

- Standard : IEEE 802.3af/at
- Number of PSE Port : 24
- System Power Consumption : Max. 26W
- Max. PoE Budget : Max. 300W@AC or 720W@DC, 30W for each PoE port
- PoE Mode : Mode A (1, 2+ & 3, 6-)
- Power Feeding Detecting Capability on PD
- PD Classification
- PD Alive Check
- PoE Scheduling
- Power Management (per port)
 - Enable/Disable PoE Per Port
 - Priority Setting Per Port
 - Power Level Setting Per Port
 - Overloading Protection

Order Information

Model Name	Description
INEO-IGM2440P-A	Industrial 24-port 10/100/1000M PoE+ with 4 x 1G SFP Slots PoE Switch with AC input with working temperature -40~75C
INEO-IGM2440P-AD	Industrial 24-port 10/100/1000M PoE+ with 4 x 1G SFP Slots PoE Switch with AC and DC dual input with working temperature -40~75C
INEO-IGM2440P-DD	Industrial 24-port 10/100/1000M PoE+ with 4 x 1G SFP Slots PoE Switch with dual DC input with working temperature -40~75C
INEO-IGM2440P-AA	Industrial 24-port 10/100/1000M PoE+ with 4 x 1G SFP Slots PoE Switch with dual AC input with working temperature -40~75C